



**SPECIFICATIONS:**

1. BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063-T6
2. ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. BASE FINISH: MILL
4. POURED CONCRETED STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END TO STEPS
5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
6. COLOR: BLACK, YELLOW, GRAY, RED, BROWN, GREEN, BLUE, TAN
7. LENGTH: 144 MAXIMUM (STANDARD)

LENGTH	QTY	COLOR

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES



190 Century Drive, Bristol, CT 06010  
Tel.: 800-457-0869, 860-589-9085  
Fax: 860-589-9081  
www.amstep.com  
e-mail: sales@amstep.com

**351ASR Anti-Slip Safety Stair Nosings**  
Ribbed Abrasive  
Short Nose

**351ASR**

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMSTEP PRODUCTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMSTEP PRODUCTS IS PROHIBITED.